

PCT

(32) Priority Dates:

(33) Priority Country:

(GB).

WORLD INTELLECTUAL PROPERTY ORGANIZATION



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 4: G01N 33/543, 33/558, 33/76 G01N 33/74		4	(11) International Publication Number: WO 88/08534
			(43) International Publication Date: 3 November 1988 (03.11.88)
(21) International	Application Number: PCT/0	GB88/00	i75) Inventors/Applicants (for US only): MAY, Keith IGB/
(22) International	Filing Date: 26 April 198	38 (26.04	(GB) 33 Molivers Lane, Bromham, Bedfordshire

(31) Priority Application Numbers: 8709873 8725457

> 27 April 1987 (27.04.87) 30 October 1987 (30.10.87)

(71) Applicant (for AU only): UNILEVER PLC [GB/GB]; Unilever House, Blackfriars, London EC4P 4BQ

(71) Applicant (for JP only): UNILEVER NV [NL/NL]; Burgemeester's Jacobplein 1, NL-3000 Rotterdam (NL).

(75) Inventors; and (75) Inventors/Applicants (for US only): MAY, Keith [GB/GB]; 33 Molivers Lane, Bromham, Bedfordshire (GB). PRIOR, Michael, Evans [GB/GB]; 330 Newton Road, Rushden, Northamptonshire (GB). RICHARDS, Ian [GB/GB]; Stonely Court, 14 Kimbolton Avenue, MK40 3AD Bedford (GB).


(74) Agent: BUTLER, David, John; Patent Division, Unilever PLC, Unilever House, Blackfriars, London EC4 4BQ (GB).

(81) Designated States: AU, JP, US.

Published

With international search report. With amended claims.

(54) Title: IMMUNOASSAYS AND DEVICES THEREFOR



(57) Abstract

An analytical test device useful for example in pregnancy testing, comprises a hollow casing (500) constructed of moisture-impervious solid material, such as plastics materials, containing a dry porous carrier (510) which communicates indirectly with the exterior of the casing via a bibulous sample receiving member (506) which protudes from the casing such that a liquid test sample can be applied to the receiving member and permeate therefrom to the porous carrier, the carrier containing in a first zone a labelled specific binding reagent is freely mobile within the porous carrier when in the moist state, and in a second zone spatially distinct from the first zone unlabelled specific binding reagent for the same analyte which unlabelled reagent is permanently immobilised on the carrier material and is therefore not mobile in the moist state, the two zones being arranged such that liquid sample applied to the porous carrier can permeate via the first zone into the second zone, and the device incorporating means, such as an aperture (508) in the casing, enabling the extent (if any) to whichthe labelled reagent becomes bound in the second zone to be observed. Preferably the device includes a removable cap for the protruding bibulous member.